



## DIGITAL RF WIRELESS FOOT SWITCH

Linemaster's Radio Frequency foot switch is available in single, twin, and triple variations to suit most applications. With up to 50 feet of range, the waterproof foot switch is a perfect fit for many applications. The release of the RF wireless is another step towards the future and also compliments the Infrared line of switches nicely. These foot switches can be factory programmed or programmed by the end user. Enjoy the freedom that the wireless has to offer. With state of the art technology and redundant signal every time, cords will be a thing of the past. Leave the hassle of cords behind and step forward with the RF Wireless Foot Switch. Only from Linemaster, American made innovation at work.



LINEMASTER Switch Corporation  
Tel (860) 974-1000

29 Plaine Hill Rd, P.O. Box 238  
Woodstock, Connecticut  
06281-0238 USA  
Fax (800) 974-FOOT(3668)



# DIGITAL RF WIRELESS FOOT SWITCH

## FEATURES

- Range: Typically 50 Feet
- 2.405-2.480 GHz, Channels 1-15
- Switch Functions: Maximum of 5
- Latency: Typically 50 milliseconds
- Transmitter Battery Life:  
400 hours @ 50% Duty Cycle Typical
- Waterproof-IP68 Degree of Protection
- Power Consumption (Transmitter): Stand-by 2ua
- Power Requirements (Receiver): 6VDC @ 200ma  
(Other voltages available)



### SINGLE TRANSMITTER

SIZE (HxWxD): 7.75 x 2.63 x 8.5 in.  
WEIGHT: 3.70 lbs. w/batteries



### TWIN TRANSMITTER

SIZE (HxWxD): 14.0 x 2.63 x 10.0 in.  
WEIGHT: 5.50 lbs. w/batteries



### TRIPLE TRANSMITTER

SIZE (HxWxD): 20.5 X 2.63 X 11.0 in.  
WEIGHT: 7.50 lbs. w/batteries



### RECEIVER

SIZE (HxWxD): 5.00 x 2.25 x 3.5 in  
WEIGHT: 0.45 lbs

Classified to IEC/UL 60601.1 Medical electrical equipment by Underwriter's laboratories, Inc. with respect to fire, shock, and mechanical hazards in accordance with IEC/UL 60601.1

Classified with respect to electric shock, fire, mechanical, and other specified hazards only, in accordance with Can/CSA C22.2 No. 60601.1

Meets EMC Directive EN60601-1-2