



SLIM-LINE SHIELDS

Engineered with an eagle eye on quality and value, the new Slim-Line foot switch from LINEMASTER® soars above the rest. With the choice of SPDT, SPDT (2 stage) or DPDT the Slim-Line foot switch is a versatile solution for applications requiring a precision lightweight or medium weight foot control. Form follows function in the Slim-Line's small size, graceful curves and patented design, while non-skid feet and raised dimples ensure positive performance. Designed to be fully submersible in water or cleaning solution. The Slim-Line foot switch is available in a reinforced polymeric material. You can count on the famous consistency and familiar action you get with every LINEMASTER® Switch.



LINEMASTER Switch Corporation
Tel (860) 974-1000

29 Plaine Hill Rd, P.O. Box 238
Woodstock, Connecticut
06281-0238 USA
Fax (800) 974-FOOT(3668)



SLIM-LINE FOOT SWITCH

EN 60529 DEGREE OF PROTECTION IP10 (IP68 UPON REQUEST)
 DRIP TIGHT • DUST TIGHT • WATERTIGHT • CORROSION RESISTANT
 SMALL LIGHTWEIGHT LOW PROFILE DESIGN

MATERIALS OF CONSTRUCTION

- Cover & base formed from light gray (PMS 427C) ABS Polymeric material
- Non-glare finish
- Silver Alloy contacts
- SPDT, DPDT, Two-Stage, Momentary operation
- Integrated adjustable strain relief clamp accommodates cord sizes from .250 Dia. to .400 Dia.




SIZE (HxWxD): 1.05 x 2.50 x 3.48 In.
 WEIGHT: 4 oz.

FEATURES & BENEFITS:

- Maximum versatility, total performance in a small package
- Rustproof and corrosion resistant
- Mounting holes provided for rigid mounting to floor or equipment
- Non-skid feet
- Raised dimples on treadle for positive traction during operation
- 10A 125-250 VAC ratings
- Designed to meet UL, CSA & CE requirements

OPTIONS:

- Custom colors and color matching available with quantity orders
- Fully submersible in water (IP68)
- Twin & Triple models available
- Full & Twin Guards as well as accessory base units available for configurations using multiple switches
- Custom connectivity options including Universal Serial Bus (USB)
- Custom cabling options
- 3A 125-250 VAC & 5A 125-250 VAC available



AGENCY APPROVALS	EN 60529 Degree of Protection	CATALOG NUMBER	DESCRIPTION	CIRCUIT	FORM	ELECTRICAL RATINGS
	IP20	SL1-S	Single Pedal/Momentary	SPDT	C	10A 125-250 VAC
		SL2-S		SPDT - 2 Stage		
		SL4-S		DPDT		
	IP68	SL1-SWBNO210*	Single Pedal/Momentary	SPDT	C	5A 125-250 VAC
		SL2-SWBNO410**		SPDT - 2 Stage		
		SL4-SWANO410**	Single Pedal/Momentary	DPDT	C	3A 125 VAC 2A 250 VAC
		SL4-SWBNO310***	Single Pedal/Momentary	DPDT	C	5A 125-250 VAC
		SL4-SWBNO410**		DPDT		

*Supplied with 10 ft., 2 conductor, 18 awg cord

**Supplied with 10 ft., 4 conductor, 18 awg cord

***Supplied with 10 ft., 3 conductor, 18 awg cord